

**MATERIAL SAFETY  
DATA SHEET**

Date of Preparation: 1/13/2010

Use in case of an emergency only (613) 996-6666

**SECTION I - PRODUCT AND PREPARATION INFORMATION** 38Y1

**Schwartz Chemical Corporation**  
777 McKay Road  
Pickering, Ontario  
L1W 3A3 (905)683-0411

Prepared by: Technical Committee

TRADE NAME: **Y1 ABS CEMENT**  
MANUFAC. CODE: **38Y1**  
PRODUCT CLASS: **ADHESIVE CLASS 3 UN 1133 PACKING GROUP II**  
WHIMIS CLASS: **B2 D2B**

**SECTION II - HAZARDOUS INGREDIENTS**

INGREDIENT	CAS NO.	%	NATURE OF HEALTH HAZARD AND ROUTE OF ENTRY	TYPE OF HAZARD	EXPOSURE LIMIT	SOURCE	OTHER HAZARDS
METHYL ETHYL KETONE	78-93-3	60-100	HARMFUL IF INHALED, IRRITANT SKIN CONTACT	ACUTE	200 PPM	TLV	
TOLUOL	108-88-3	7-13	HARMFUL IF INHALED, IRRITANT SKIN CONTACT	ACUTE	100 PPM	TLV	

**SECTION III - PHYSICAL DATA**

<b>ODOUR AND APPEARANCE</b>	<b>PH VALUE</b>	<b>PERCENT VOLATILE BY VOLUME</b>	<b>EVAPORATION RATE</b>
KETONE		72%	GREATER THAN BUTYL ACETATE
YELLOW		<b>VOC LEVEL 410 g/L</b>	
<b>BOILING POINT</b>		<b>FREEZING POINT</b>	<b>SPECIFIC GRAVITY</b>
80°C		°C	1.00

**SECTION IV - FIRE AND EXPLOSION HAZARDS**

FLAMMABILITY CLASSIFICATION /	FLASHPOINT	HAZARDOUS COMBUSTION PRODUCTS
Class 3, Division 2	7- °C	ON COMBUSTION, DENSE SMOKE CONTAINING CARBON MONOXIDE, CARBON DIOXIDE AND HYDROGEN CYANIDE
	TAG CUP	<b>EXTINGUISHING MEDIA</b>
		Foam, dry chemical, carbon dioxide or any class B extinguishing agent

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Vapours may ignite explosively. Vapours may spread long distances. Prevent build-up of vapours. Extinguish all pilot lights and turn off heaters, non-explosion-proof electrical equipment and all other sources of ignition. Keep away from and do not store or use near heat, sparks or flames caused by such sources as electricity, static discharge, welding, grinding or flamecutting operation. Ground all equipment. Use spark-proof tools and conductive shoes to avoid sparking hazards.

**SPECIAL FIREFIGHTING PROCEDURES**

Exposure to vapours or products of combustion should be avoided. Self-contained breathing apparatus is recommended. Vapours may form an explosive mixture with air. Closed containers may rupture when exposed to extreme heat.

**MATERIAL SAFETY  
DATA SHEET**

Date of Preparation: 1/13/2010

Use in case of an emergency only (613) 996-6666

SECTION V - HEALTH HAZARD DATA: TOXICOLOGICAL PROPERTIES AND FIRST AID MEASURES		38Y1
<b>ACUTE EFFECTS OF OVEREXPOSURE</b>	<b>EMERGENCY AND FIRST AID PROCEDUES</b>	
<p><b>INHALATION:</b> Excessive exposure to vapours or spray mists can result in headache, dizziness, incoordination and loss of consciousness. Irritation of the eyes, nose, throat and lungs can also occur when exposed to high vapour concentrations. Some reports have associated repeated and prolonged occupational overexposure to solvents with permanent nervous system damage.</p> <p><b>EYE CONTACT:</b> This material can cause eye irritation. The effects are usually reversible.</p> <p><b>SKIN CONTACT:</b> This material may cause defatting and irritation of skin (Dermatitis) upon prolonged or repeated contact.</p> <p><b>INGESTION:</b> Swallowing can cause nausea, vomiting, diarrhea and loss of consciousness.</p>	<p><b>INHALATION:</b> Remove victim to fresh air. Restore breathing. Treat symptomatically. Consult a physician.</p> <p><b>SPLASH (EYES):</b> Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment.</p> <p><b>SPLASH (SKIN):</b> Wash affected areas with soap and water. Remove contaminated clothing.</p> <p><b>INGESTION:</b> Drink 1 or 2 glasses of water to dilute. <b>DO NOT INDUCE VOMITING.</b> Consult a physician or Poison Control center immediately. Treat symptomatically.</p>	
<b>CHRONIC EFFECTS OF OVEREXPOSURE</b>	<b>IRRITANT</b>	<b>SENSITIZER</b>
n/av	YES: Skin and Eye	YES: Skin
<b>SECTION VI - REACTIVITY DATA</b>		
<b>STABILITY:</b>	<b>HAZARDOUS POLYMERIZATIONS:</b>	
Stable	Will not occur	
<b>INCOMPATIBILITY: (Materials to avoid)</b>	<b>CONDITIONS TO AVOID:</b>	
Oxidizing compounds	Vapour concentrations	
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	Ignition sources	
None known		
<b>SECTION VII - SPILL OR LEAK PROCEDURES</b>		
<b>STEPS TO BE TAKEN in case material is Released or Spilled</b>	<b>WASTE DISPOSAL METHOD</b>	
Restrict access to area. Remove all sources of ignition. Ventilate area. Absorb spill with an absorbent material such as vermiculite or sand and place material into a closed container. If a large spill, dike area to prevent this material from entering water systems or sewers. Wear protective equipment during cleanup.	Dispose of this material in accordance with Federal, Provincial, and Municipal regulations.	
<b>SECTION VIII - SPECIAL PROTECTION INFORMATION</b>		
<b>PERSONAL PROTECTION EQUIPMENT</b>		
<b>PROTECTIVE GLOVES:</b>	<b>EYE PROTECTION:</b>	
Chemical resistant gloves made of Viton should be used. Gloves made of nitrile, neoprene or rubber may be used for exposure of short duration.	Chemical safety goggles should be worn to prevent eye contact. A face shield may also be necessary.	
<b>RESPIRATORY PROTECTION:</b>	<b>OTHER PROTECTIVE EQUIPMENT:</b>	
An organic vapour cartridge respiratory mask shall be worn to prevent the inhalation of vapours or spray mist when the TLB or PEL is exceeded. If respiratory protection is required, institute a complete respiratory protection program. Refer to the CSA Standard Z94.4 M1982 "Selection, Care and Use of Respirators" available from the Canadian Standard Association, Rexdale, Ontario. M9W 1R3	Eye wash fountain and safety showers must be available in areas where this material is used. Wear protective clothing to prevent skin contact.	
	<b>ENGINEERING CONTROLS - VENTILATION:</b>	
	General (dilution) ventilation is required during normal use. Local exhaust ventilation may be required during certain operations to keep exposure level below the limit listed in Section II of this data sheet.	
<b>SECTION IX - SPECIAL PRECAUTIONS</b>		
<b>PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING</b>	<b>OTHER PRECAUTIONS</b>	
<p><b>STORAGE:</b> Keep storage area separate from populated work areas. Store in a cool, dry, well ventilated area, out of direct sunlight and away from incompatible materials and any source of ignition. Ventilation fans and electrical equipment should be non-sparking.</p> <p><b>HANDLING:</b> Avoid prolonged or repeated inhalation of vapours or spray mist. Avoid prolonged or repeated skin contact. Ground and bond equipment and container to prevent a static charge build-up.</p> <p><b>ATTENTION:</b> Emptied containers may retain hazardous residue and explosive vapours. Keep away from heat, sparks and flames. Do not cut puncture or weld near this container. Follow label warning until container is thoroughly cleaned or destroyed.</p>		