



**BARCLAY**  
S A L E S  
• EST. 1971 •

# Safety Data Sheet

## Plumb Rite Silicone - White

### Section 1. Identification

Product Identifier            Plumb Rite Silicone - White  
Synonyms                      142946  
Manufacturer Stock  
Numbers                        142946

Recommended use            Refer to Technical Information  
Uses advised against        Refer to Technical Information

Manufacturer Contact  
Address                        Barclay Sales  
                                     1441 Kebet Way, Port  
                                     Coquitlam, BC V3C 6L3

Phone  
(604)-945-1010

Emergency Phone  
(800) 424-9300  
CHEMTREC

Fax  
(604)-945-3030  
or  
(604)-648-8854

### Section 2. Hazards Identification

Classification                N/A  
Signal Word  
Pictogram  
Hazard Statements            N/A  
Precautionary Statements  
Response                      N/A  
Prevention                    Use only outdoors or in a well-ventilated area.  
Storage                        N/A

Disposal

N/A

Ingredients of unknown toxicity

0%

Hazards not Otherwise Classified

GHS Classification

Not a hazardous substance or mixture.

GHS Label Element

Not a hazardous substance or mixture.

Other hazards

None known

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
64742-46-7	Distillates (petroleum), hydrotreated middle	5% - 10%
7631-86-9	Amorphous silica	5% - 10%

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-Aid Measures

Eye Contact

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes while holding the eyelids open. Obtain medical attention.

Skin Contact

No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.

Inhalation

If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.

Ingestion

If irritation or discomfort occur, obtain medical advice.

Comments

Treat according to person's condition and specifics of exposure.

## Section 5. Fire Fighting Measures

Suitable Extinguishing Media

On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.

Unsuitable Extinguishing Media

None known

Special Fire Fighting Procedures

Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire or Explosion Hazards

None known

## Section 6. Accidental Release Measures

**Steps to be taken in case of spill or release** Observe all personal protection equipment recommendations in Sections 5 and 8. Wipe or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

**Note** See Section 8 for information about personal protective equipment for spills. Contact Accumetric, LLC if additional information is required.

## Section 7. Handling and Storage

**Storage** Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

**Handling** Use adequate ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact.

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Distillates (petroleum), hydrotreated middle	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
	Amorphous silica	10 mg/m <sup>3</sup>	6 mg/m <sup>3</sup>	Not Est.

**Personal Protective Equipment** Goggles, Gloves

**Engineering Controls** Local Ventilation: None should be needed  
General Ventilation: Recommended

**Respiratory Protection** No respiratory protection should be needed.

Suitable Respirator: None should be needed.

**Eye Protection** Use proper protection - safety glasses as a minimum.

**Skin Protection** Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves:

Precautionary Measures

Handle in accordance with good industrial hygiene and safety practices.

Comment

Avoid eye contact. Avoid skin contact. Use reasonable care.

Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection.

When heated to temperatures above 150C (300F) in the presence of air, product can form formaldehyde vapors. Physical and health hazard information is readily available on the Material Safety Data Sheet. When heated to temperatures above 150C in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose throat, skin and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limit for formaldehyde.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

**Section 9. Physical and Chemical Properties**

Physical State	Paste
Color	Refer to product label
Odor	Acetic Acid
Odor Threshold	No data available
Solubility	No data available
Partition coefficient Water/n-octanol	No data available
VOC%	23 g/L
Viscosity	Not applicable
Specific Gravity	1.007
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	>212F >100C
FP Method	Closed Cup
pH	Not applicable
Melting Point	No data available
Boiling Point	Not applicable
Boiling Range	Not applicable
LEL	N/A

UEL	N/A
Evaporation Rate	Not applicable
Flammability	Not classified as a flammability hazard
Decomposition Temperature	No data available
Auto-ignition Temperature	No data available
Vapor Pressure	Not applicable
Vapor Density	No data available

**Note** The above information is not intended for use in preparing product specifications. Contact Soudal before writing specifications.

## Section 10. Stability and Reactivity

Chemical Stability	Stable
Hazardous polymerization	Will not occur
Conditions to avoid	None known
Materials to Avoid / Incompatibility	Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form as described in Section 8.
Hazardous Decomposition Products	Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds Formaldehyde Silicon dioxide

## Section 11. Toxicological Information

**Special Hazard Information on Components** No known applicable information.

## Section 12. Ecological Information

Fate and Effects in Waste Water Treatment Plants	Complete information is not yet available.
Environmental Effects	Complete information is not yet available.
Environmental Fate and Distribution	Complete information is not yet available.

## Section 13. Disposal

Waste Disposal Method	We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.  This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.
RCRA Hazard Class (40 CFR 261)	When a decision is made to discard this material, as received, is it classified as a hazardous waste? NO  State or local laws may impose additional regulatory requirements regarding disposal.

## Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	Not regulated
DOT Classification	Not regulated
Packing Group	Not regulated
Ocean Shipment (IMDG)	Not subject to IMDG code.
Air Shipment (IATA)	Not subject to IATA regulations.

## Section 15. Regulatory Information

TSCA Status	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Title III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 311/312 Hazard Class	Acute: No Chronic: No Fire: No Pressure: No Reactive: No
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
Note	Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

California Proposition 65

This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm:  
None known

New Jersey

Dimethyl siloxane, hydroxy-terminated (70131-67-8)  
Ethyltriacetoxysilane (17689-77-9)  
Methyltriacetoxysilane (4253-34-3)  
Silica, amorphous (7631-86-9)  
Hydrotreated middle petroleum distillates (64742-46-7)

Pennsylvania

Dimethyl siloxane, hydroxy-terminated (70131-67-8)  
Silica, amorphous (7631-86-9)  
Hydrotreated middle petroleum distillates (64742-46-7)

**Section 16. Other Information**

Revision Date

2/10/2020

Disclaimer

The data contained herein is based upon information that Soudal believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.